

SF-P15/72

335-350W

156.75 × 156.75mm cells 72



Polycrystalline

PERC Full Cell Module

Max Power out: 350W

Max Efficiency: 18.00%

Power Tolerance: 0~+5W



SMBB Technology

Better light trapping and current collection to improve module power output and reliability



Reduced Hot Spot Loss

Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.




High energy generation, low LCOE

Low Pmax temp coefficient increases energy production

Superior Warranty

- 15-year material & technology warranty
- 25-year linear power output warranty




Comprehensive Products and System Certificates

- IEC/EN61215-1:2021 & IEC/EN61215-2:2021
- IEC/EN61730-1:2016 & IEC/EN61730-2:2016
- UL61730-1:2017 & UL61730-2:2017
- UL61215-1:2017 & UL61215-2:2017
- IEC 61701:2020-Saltmist
- IEC 62716:2013-Ammonia
- IEC 62804:2020-PID
- IECEE CertificateBody (CB)
- UKCA:EN61730-2018
- ISO9001 & ISO14001 & ISO45001



Engineering Drawings



Structural Parameter

Dimensions of Module	1956×992×35mm
Weight	19kg
Packing	31/pallet, 840/40hq
Glass	High transparency solar glass 3.2mm
Backsheet	White
Frame	Anodized aluminum alloy & Custom color accepted
J-Box	IP67 Rated
Cable	4.0mm ² , 1100mm
Bypass Diodes	3pcs
Wind/ Snow Load	2400Pa/5400Pa
Connector	MC4 Compatible

Electrical Specification

(STC: Irradiance 1000W/m², cell temperature 25°C, AM1.5G — NOCT: Irradiance 800W/m², Ambient temperature 20°C, Wind speed 1m/s)

Module Type	SF-P15/72335		SF-P15/72340		SF-P15/72345		SF-P15/72350	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax) [W]	335	248.86	340	252.75	345	256.68	350	260.99
Maximum Power Voltage (Vmp) [V]	38.00	35.10	38.20	35.30	38.90	35.60	39.20	35.90
Maximum Power Current (Imp) [A]	8.82	7.09	8.90	7.16	8.87	7.21	8.93	7.27
Open Circuit Voltage (Voc) [V]	46.40	43.10	46.60	43.30	47.30	44.00	47.60	44.20
Short Circuit Current (Isc) [A]	9.41	7.60	9.49	7.66	9.61	7.73	9.68	7.79
Module Efficiency [%]	17.30		17.50		17.80		18.00	
Cell Type [mm]	Poly 156.75×156.75, 72 cells							
Operational Temperature [°C]	-40~+85°C							
Maximum System Voltage	1500V DC							
Max Series Fuse Rating	15A							

Temperature Ratings

Nominal Operating Cell Temperature	45±2°C
Temperature Coefficient of Isc	+0.06%/°C
Temperature Coefficient of Voc	-0.30%/°C
Temperature Coefficient of Pmax	-0.39%/°C

Curve Diagram

